



1C20-101



1C26-101

ECONOMY MECHANICAL THERMOSTATS

Reliable Performance in an Attractive Design

FEATURES

- Rugged snap-action contacts.
- Adjustable heat anticipator.
- Bi-Metal thermometer.
- Heat/Cool model includes switching subbase.
- Heat/Cool model compatible with Electric Heat systems.
- Classic White color.

SPECIFICATIONS

Anticipation Rating, Heating Adjustable from 0.15 to 1.2 Amps
 Anticipation Rating, Cooling Fixed
 Differential, Heating 2°F (1.1°C)
 Differential, Cooling 4°F (2.2°C)
 Dimensions 3³/₄"H x 2⁷/₈"W x 1¹/₂"D
 Dimensions, Switching Models . . 3³/₄"H x 3¹/₈"W x 1⁵/₈"D
 Electrical Rating mV to 30V, 50/60 Hz or DC

PARTS AND ACCESSORIES See end of this section for parts and accessories

- Thermostat Guards — see pages 23-24
- Wallplate F61-2499 — 5¹/₈"H x 5"W

TECHNICAL HELP

Configuration/Wiring See page 198



Model Number	Typical Application	Stages Heat/Cool	System Switch	Fan Switch	Contacts	Anticipation Heat/Cool	Range	Shape	Terminals
1C20-101	Heat Only ③	1	None ①	None	Snap-Action	Adjustable	50-90°F (10-32°C)	Vertical	R, W
1C20-102	Heat Only	1	None	None	Snap-Action	Adjustable	50-90°F (10-32°C)	Vertical	R, W
1C21-101	Cool Only	1	None	None	Snap-Action	Fixed	50-90°F (10-32°C)	Vertical	R, Y
1C26-101	Heat/Cool ② ③	1/1	Heat-Off-Cool	Auto-On	Snap-Action	Adjustable/Fixed	50-90°F (10-32°C)	Vertical	RC, RH, W, Y, G, O, B, A

① Lowest temperature setting is "OFF" position

② Includes optional "A" terminal connection for Electric Heat systems that require the thermostat to energize the Blower (G terminal) on a call for heat

③ Includes F61-2499 wall mounting plate to cover marks left by previous thermostat