

ADJUSTMENT PROCEDURE FOR:

9200 STS *Soft-Touch* SHORT HANDLE TOOLS 12" OVERALL LENGTH


This tool is adjusted at the factory and no further adjustment should be required.

Should the tools, through extended use, require adjustment, wear in the parts may be compensated for as follows:

1. Close tool handles until pre-load is reached (this is the point at which jaws butt).
2. Measure the distance between the outside of the handles at the end of the handle grips. Dim X is the correct distance.
3. To increase the pre-load setting, remove the #6-32 eccentric lock screw and rotate counter clockwise to increase the handle pre-load and clockwise to decrease handle pre-load. Re-install the #6-32 lock screw in the appropriate hole which most closely yields the desired handle dimension.
4. Recheck the set distance after making three crimps.
5. Check the crimps with the crimp gauge provide. If satisfactory crimps do not result, the tool is likely worn and should be replaced.

In addition, always remember to:

1. Check tool calibration at least daily. It is recommended that at least the first and last crimp of the day are tested.
2. Never exceed the specified handle distance when adjusting your crimp tool. Premature wear will result.
3. Lubricate linkages on a regular basis to maximize tool life.



LIMITED WARRANTY

Rostra warrants that its product sold under the *Soft-Touch* trade name are free from defects in workmanship and materials under normal use and service. This warranty does not cover defects or damage arising from improper installation, lack of or improper maintenance, improper storage, shipping and handling, or ordinary wear and tear, misuse, abuse, accident, unauthorized service, or use with unauthorized non-standard products or parts. The only liability of the company in tort or contract whether under this warranty or otherwise shall be limited to the repair or replacement of any product or component part which shall prove defective as covered by this warranty within one year after delivery to the original purchaser from the company. The manufacturer will not pay for the cost of repair performed other than in accordance with this warranty. The product or component part believed to be defective as covered by this warranty should be sent to the point of purchase for return to the manufacturer, and should include your name and address, for identification of the product or component part and a brief description of the defect. Shipping charges must be prepaid, for examination and; in the event such examination reveals a defect covered by this warranty, the product will be repaired or replaced. This warranty is in lieu of all other express warranties. To the extent permitted by law, all implied warranties are limited to the duration of this warranty. The manufacturer shall not be liable for the incidental or consequential damages. Some states do not allow limitations or exclusions may not apply to you. This warranty gives you the specific legal rights, and you may also have other rights which vary state to state.

This warranty is null and void if the date coded adjustment sticker is removed

| CATALOG NUMBER | DESCRIPTION | DIM X |
|----------------|-------------|---------------|
| 9201 STS | 3/8" | 5" ± 1/4" |
| 9202 STS | 1/2" | 6 1/2" ± 1/4" |
| 9203 STS | 3/4" | 7 1/2" ± 1/4" |
| 9207 STS | 5/8" | 6 1/2" ± 1/4" |

