

THERMOPLASTIC AUTOMATIC SUBMERSIBLE SUMP PUMPS

These sump pumps provide carefree performance and quiet operation. Each is corrosion-resistant with a screened top inlet. Discharge features a unique 1-1/4" inside thread with a 1-1/2" outside thread for maximum versatility on replacement jobs.

FPOS3250A, FPOS2450A



Made In The U.S.A. UL SSPMA Certified

FEATURES

- Automatic submersible sump pump
- Maximum pumping – see performance chart on following page
- Corrosion-resistant composite construction
- 115V overload protected motor
- Automatic or manual operation
- 8' grounded power cord
- 1-1/4" or 1-1/2" discharge pipe size

FPOS3250A

1/2 HP

BEST 3 Year Warranty

- Maximum pumping capacity to 3630 gallons per hour
- Can be used in narrow 10" diameter sump basin
- Most popular submersible series

FPOS3200A, FPOS2400A



Made In The U.S.A. UL SSPMA Certified

FPOS3200A

1/2 HP

BEST 3 Year Warranty

- Maximum pumping capacity to 3630 gallons per hour
- Can be used in 14" diameter sump basin
- Most popular submersible series

FPOS2450A

1/3 HP

Better 2 Year Warranty

- Maximum pumping capacity to 3150 gallons per hour
- Can be used in narrow 10" diameter sump basin

FPOS2400A

1/3 HP

Better 2 Year Warranty

- Maximum pumping capacity to 3150 gallons per hour
- Can be used in 14" diameter sump basin

FPOS1800A



Made In The U.S.A. UL SSPMA Certified

FPOS1800A

1/4 HP


Good 1 Year Warranty

- Maximum pumping capacity to 2880 gallons per hour
- Can be used in 14" diameter sump basin

PERFORMANCE INFORMATION (Based on using 1-1/4" discharge pipe)

Rating	Warranty (years)	Model	HP	Switch Type	Min. Sump Diameter	Float Switch		Performance - Gallons per Hour at Discharge Head in Feet					Maximum Lift (no flow)
						On	Off	0'	5'	10'	15'	20'	
EXCLUSIVE	LIFETIME	FPOS6000A	3/4	Float	12.6"	13.7"	4.7"	7000	6000	5040	3840	2340	25 ft.
BEST	3	FPOS3250A	1/2	Vertical	10"	8"	3.5"	3630	3200	2700	2000	1200	24 ft.
BEST	3	FPOS3200A	1/2	Float	14"	14"	6"	3630	3200	2700	2000	1200	24 ft.
Better	2	FPOS2450A	1/3	Vertical	10"	8"	3.5"	3150	2760	2160	1410	-	20 ft.
Better	2	FPOS2400A	1/3	Float	14"	14"	6"	3150	2760	2160	1410	-	20 ft.
Good	1	FPOS1800A	1/4	Float	14"	12.5"	4.5"	2880	2280	1620	660	-	18 ft.

TYPICAL APPLICATION




ACCESSORIES (sold separately, see page 10)

Required:

Check Valve	FP0026-6D or FP0026-10
Flood Alarm	FPW217-242
Discharge Hose Kit	FP0012-6F 1-1/4" x 24'
	or
	FP150-24 1-1/2" x 24'

Optional: (see page 8)

Battery Back-Up	FP1800DCC or FP2800DCC
-----------------	------------------------



DID YOU KNOW?

If you currently have a pedestal pump, it can quickly and easily be replaced with a submersible. A submersible sump pump has many advantages over a pedestal pump, such as: quieter operation, more product selection from horsepower to gallons of water per hour moved, and it's safer because the pump is fully submersed rather than extending outside the sump pit.

DID YOU KNOW?

If you have a sump pump you should consider the purchase of a Flotec Emergency Back-Up Sump Pump System. These systems are a back-up in case of power loss or primary sump pump failure to protect your home and valuables. Flotec offers 2 systems: FP1800DCC and FP2800DCC along with the supporting batteries and acid solutions. Please ask your retailer or call customer service at 1-800-365-6832 for assistance.

DID YOU KNOW?

When replacing a sump pump, you should always replace your check valve.