

# SEWAGE/EFFLUENT PUMPS

Rugged, sewage and effluent pumps are capable of handling solids up to 2". Available in cast iron or engineered composite designs for a variety of wastewater applications. Tested and certified to SSPMA standards. Ideal for mound systems, leaching fields, effluent gravity sewers, laundry facilities, underground parking, grain storage and general dewatering.



Made in The U.S.A.

## FPSE3601A

1/2 HP

EXCLUSIVE Full Lifetime Warranty

- Heavy-duty, rugged cast iron automatic submersible sewage pump
- Capable of handling 2" solids
- Maximum pumping capacity up to 9000 gallons per hour
- High efficiency motor with overload protection
- Includes by-pass float switch for automatic or manual operation
- 2" discharge meets standard code approvals
- 10' power cord for easy installation (also available with 20' power cord model FPSE3601A-20)



Made in The U.S.A.

## FPSE3200A

4/10 HP

Better 1 Year Warranty

- Automatic submersible sewage pump
- Capable of handling 2" solids
- Maximum pumping capacity up to 5250 gallons per hour
- Durable, corrosion-resistant thermoplastic construction
- High efficiency motor with overload protection
- 2" discharge meets standard code approvals
- Includes 8' power cord



Made in The U.S.A.

## FPSE2800A

1/3 HP

Better 1 Year Warranty

- Automatic submersible effluent/dewatering pump
- Capable of handling 3/4" solids
- Maximum pumping capacity up to 3600 gallons per hour
- Thermoplastic construction
- High efficiency motor with overload protection
- Includes 15' power cord

### PERFORMANCE INFORMATION

Rating	Warranty (years)	Model	HP	Type	Min. Sump Diameter	Performance - Gallons per Hour at Discharge Head in Feet						Maximum Lift (no flow)
						0'	5'	10'	15'	20'	25'	
EXCLUSIVE	LIFETIME	FPSE3601A	1/2	Sewage	18"	9000	7320	5400	2700	-	-	18 ft.
Better	1	FPSE3200A	4/10	Sewage	18"	5250	3900	2550	960	-	-	18 ft.
Better	1	FPSE2800A	1/3	Effluent	18"	3600	3180	2700	2100	1500	750	29 ft.