

WATERFALL/UTILITY PUMPS

Waterfall/Utility pumps are multi-functional and can be used as utility pumps or to create streams and waterfalls in your garden pond. With thermoplastic and stainless steel construction to choose from, these pumps meet your most demanding application for either use.

FPOS4100X



Made In Italy   

FPOS4100X

1/2 HP

BEST 2 Year Warranty

- Pumps up to 4100 gallons per hour
- Oil free motor – safe for fish and plants
- Complete stainless steel construction – superior corrosion resistance
- Dual ball bearing design – quiet, long lasting, years of trouble-free service
- Premium ceramic seal design – allows for continuous operation
- High performance – ideal for waterfalls and streams
- 15' grounded power cord
- Includes 1-1/4" x 1" NPT adapter

FPOS3000X, FPOS2300X, FPOS1200X



Made In Italy   

FEATURES

- Pumps up to 3000 gallons per hour – see performance chart on following page
- Oil free motor – safe for fish and plants
- Engineered composite, stainless steel construction – superior corrosion resistance
- Dual ball bearing design – quiet, long lasting, years of trouble-free service
- High performance – ideal for waterfalls and streams
- 15' grounded power cord
- Can be used with Flotec garden pond accessories
- Includes three discharge fittings: 1/2", 3/4" and 1" barbed hose, 1" reducer, and garden hose adapter

FPOS3000X

4/10 HP

BEST 1 Year Warranty

- Pumps up to 3000 gallons per hour
- Engineered composite, stainless steel construction – superior corrosion resistance
- Premium ceramic seal design – allows for continuous operation

FPOS2300X

3/10 HP

Better 1 Year Warranty

- Pumps up to 2300 gallons per hour
- Composite, stainless steel construction – eliminates corrosion
- Premium ceramic seal design – allows for continuous operation

FPOS1200X

1/6 HP

Better 1 Year Warranty

- Pumps up to 1200 gallons per hour
- Corrosion-resistant construction

PERFORMANCE INFORMATION

Rating	Warranty (years)	Model	HP	Watts	Inlet	Outlet	Performance - Gallons per Hour at Discharge Head in Feet						Maximum Lift (no flow)
							0'	5'	10'	15'	20'	25'	
BEST	2	FPOS4100X	1/2	800	Screened	1-1/4" w/ multiple fittings	4100	3600	3000	2400	1650	900	30 ft.
BEST	1	FPOS3000X	4/10	350	Screened	1-1/4" w/ multiple fittings	3000	2500	1900	1320	750	-	25 ft.
Better	1	FPOS2300X	3/10	275	Screened	1-1/4" w/ multiple fittings	2300	1975	1425	850	300	-	22 ft.
Better	1	FPOS1200X	1/6	180	Screened	1-1/4" w/ multiple fittings	1200	1000	675	400	-	-	20 ft.

CYCLONE™ PUMP

The CYCLONE™ pumping system is designed for every day or emergency use. Perfect for transferring or removing unwanted water from waterbeds, aquariums, or non-draining sinks.



Made in The U.S.A.

FPOF360AC

1/12 HP

Better 1 Year Warranty

CYCLONE™

- Multi-purpose pump designed for emergency dewatering, draining aquariums, waterbeds and clogged sinks
- Maximum pumping capacity up to 350 gallons per hour
- Self-priming at 8-10' vertically
- Corrosion-resistant, compact, portable
- Includes 6' garden hose, PUD-L-SCOOP® suction attachment and 6' power cord
- Pumps floor dry to 1/8"

PERFORMANCE INFORMATION

Rating	Warranty	Model	HP	Performance - Gallons per Hour at Discharge Head in Feet						Maximum Lift (no flow)
				0'	5'	10'	20'	30'	40'	
Better	90 days	FPOF360AC	1/12	350	320	300	240	145	62	43 ft.